Cummins Inc.

EXECUTIVE ORDER U-R-002-0162-1 New Off-Road

New Off-Road Compression-Ignition Engines

Pursuant to the authority vested in the Air Resources Board by Sections 43013, 43018, 43101, 43102, 43104 and 43105 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following compression-ignition engine and emission control system produced by the manufacturer are certified as described below for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY	DISPLACEMENT (liters)	FUEL TYPE	USEFUL LIFE (hours)		
2003	3CEXL0275AAA	4.5	Diesel	8000		
SPECIAL FEATURES & EMISSION CONTROL SYSTEMS			TYPICAL EQUIPMENT APPLICATION			
Direct Diesel Injection, Turbocharger, Engine Control Module			Loader, Tractor, Dozer, Pump, Compressor			

The engine models and codes are attached.

The following are the exhaust certification standards (STD), or family emission limit(s) (FEL) as applicable, and certification levels (CERT) for hydrocarbon (HC), oxides of nitrogen (NOx), or non-methane hydrocarbon plus oxides of nitrogen (NMHC+NOx), carbon monoxide (CO), and particulate matter (PM) in grams per kilowatt-hour (g/kw-hr), and the opacity-of-smoke certification standards and certification levels in percent (%) during acceleration (Accel), lugging (Lug), and the peak value from either mode (Peak) for this engine family (Title 13, California Code of Regulations, (13 CCR) Section 2423):

RATED POWER	EMISSION STANDARD		EXHAUST (g/kw-hr)				OPACITY (%)			
CLASS	CATEGORY	;	нс	NOx	NMHC+NOx	co	PM	ACCEL	LUG	PEAK
75 ≤ kW < 130	Tier 2	STD	N/A	N/A	6.6	5.0	0.30	20	15	50
		FEL	N/A	N/A	6.4	N/A	N/A	N/A	N/A	. N/A
		CERT			5.5	1.0	0.19	14	2	29

BE IT FURTHER RESOLVED: That the family emission limit(s) (FEL) is an emission level declared by the manufacturer for use in any averaging, banking and trading program and in lieu of an emission standard for certification. It serves as the applicable emission standard for determining compliance of any engine within this engine family under 13 CCR Sections 2423 and 2427.

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has submitted the information and materials to demonstrate certification compliance with 13 CCR Section 2424 (emission control labels), and 13 CCR Sections 2425 and 2426 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

This Executive Order hereby cancels and replaces Executive Order U-R-002-0162 dated November 26, 2002.

Executed at El Monte, California on this 474 day of May 200

Allen Lyons, Chief

Mobile Source Operations Division

U-R-002-0162-1

Cummins Inc. Manufacturer: Engine category: Nonroad Over 50 Hp
EPA Engine Family. 3CEXL0275AAA

Mfr Family Name: A852

New Submission Process Code:

ol 930		
on L	O O	့ ်
on C	00	ं ह
9.Emission Control Device Per SAE J1930	DDI,TO,EC/ DDI,TO,EC	DDI,TC,EC DDI,TC,EC
9.En		
۵		
sidne		
3ate ak tc	7	4 C
8.Fuel Rate: /hr)@peak tor	33.7	83.4 0.00
8.Fuel Rate: lbs/hr)@peak torque		
EQ ()		
粪		
7.Fuel Rate: mm/stroke@peal torque		
7.Fuel Rate: m/stroke@pe torque	8 5	06 86
/Fue stro		
, mm		
₩ (00	<u> </u>
Torque @ RP (SEA Gross)	305@1500 305@1500	305@1500 305@1500
S due	6 6	(A) (B)
6.Torque @ RPM (SEA Gross)	8	සි පි
9		
₽ ~		
5.Fuel Rate: (lbs/hr) @ peak HP (for diesels only)		
5.Fuel Rate: s/hr) @ peak or diesels on	47.8 44.5	46.1 44.0
5.Fu /hr) (r die	4 4	7
edl)		
<u> -</u>		
4.Fuel Rate: mm/stroke @ peak HP (for diesel only)		
4.Fuel Rate: stroke @ pea or diesel only	8 C	ry o
Fuel oke (dies	ထော	ထားထ
4.1 Vstrc (for		
Ē		
APM 188)	10@2500 10@2200	10@2500 10@2200
.BHP@RPN SAE Gross)	8 8	10@2500 10@2200
3.BHP@RPM (SAE Gross)	110@2500 110@2200	<u> </u>
	7	
-		
ode	보호	<u> </u>
∑ .	QSB4.5-30-T QSB4.5-30-T	3\$B4.5-30-T 3\$B4.5-30-T
gin	7 7	# H
En .	88	888
		_
de	e .∠	등 성
ပ္သိ	菱菱	<u> </u>
yine	E E	F. F
LEngine Code 2.Engine Model	8263,FR91166 8343;FR91167	8041,FR91221 8042;FR91222
- '	8 8	88